



## Product Information

Introducing our Euro SnapUp.

Our multi-layered PET/PP structure provides the ideal balance of rigidity and flexibility. With stable curl control and exceptional blockout capabilities, your prints will always look their best.

Experience high-quality image reproduction with stunning color expression that will truly make your signage stand out. Our print media is compatible with a range of inks, including eco-solvent, solvent, UV curable, and HP Latex inks. Plus, it's certified for use with HP Latex Inks, ensuring top-notch results every time.

It is also **PVC-free**, making it environmentally friendly.

## Shelf Life

1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

## Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

## Technical Data

Carrier	PP/PET Hybrid
Backing	Grey
Thickness	420 gsm (+/- 5%)
Finish	Satin
Temperature durability	-30 up to +80°C
Compatibility	Eco, Solvent, UV and Latex

## Standard Dimensions

914mm (wide) x 30m (long)  
1067mm (wide) x 30m (long)

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.