



Product Information

This microporous coated banner boasts a glossy finish, ensuring instant drying and delivering high-quality images that pop.

What sets it apart is its multi-layered coating with PP+PET+PP, providing exceptional blockout, stable curl balance, and the perfect amount of stiffness.

Compared to ordinary lightweight banners, our product offers significantly higher rigidity, ensuring flatness and meeting the highest standards for brilliant color reproduction.

It is also **PVC-free**, making it environmentally friendly.

Shelf Life

1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

Technical Data

Carrier	PP/PET Hybrid
Backing	Grey
Thickness	395 gsm (+/- 5%)
Finish	Gloss
Temperature durability	-30 up to +80°C
Compatibility	Pigment, Dye, UV and Latex

Standard Dimensions

914mm (wide) x 30m (long)
1067mm (wide) x 30m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.