


**ET7-102 0.36W 2835 SMD 2LED Module**
**CE ROHS IP67**

**ET7-102 : 0.36W**

1. Adopt TOP 2835 SMD LED, no light spots, with a low lumen recession and good consistency.
2. 2835 LED SMD With a low power consumption and high lumen value, 22-55lm/LED, a long lifespan maintenance-free.
3. With a plastic injection technique for outer cover, this unique structure grants a better cooling effect. UL 94V0 ABS.
4. IP Rate: IP67 waterproof
5. DC 12V low voltage input, reliable and safe.
6. Adopt series-parallel connection circuit, 20/40pcs per string, if 40pcs connect together must be on the each end of string connect DC12V , each module could be singled out.

**Application**

This product is applicable for 10-20cm glowing character, advertisement board, round light box or local lighting.

Photometric Characteristics	
Model	ET7-102
Led Type	2835 SMD LED
LED Brand	Chip from Epistar
Viewing Angle	120°
Luminous Flux (Lm)	22 - 55lm
LED Qty	2PCS
Lifespan	50,000H
Working Voltage	DC12V
Consumption	0.36W
Driving Method	CV
Stand Length in Serial Connection	40pcs
Maximum Length in Serial Connection	≤40pcs
Shell	White ABS
Dimension	L28mm*W7mm*H4mm
IP Degree	IP67
Store Temperature	-50°C ~ +60°C

**MTX2835-2-X**
**CE ROHS**