

# **SWIFT GLOSS**Item no. **EV-STM-GL**

# **Product Information**

The Swift Gloss is monomeric PVC laminate film that is a great soution for short-term applications on flat surfaces in interior and exterior applications.

With a permanent clear solvent-based acrylic adhesive, it provides up to 2 year of durability. Ideal for facias, building signage, and window graphics.

# **Shelf Life**

1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

# **Recommendations for Laminating**

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

## **Technical Data**

**Carrier** Monomeric calendered PVC film

**Thickness** 100 µ (+/- 5%)

Adhesive Permanent clear solvent-based acrylic

**Liner** Single-sided PE coated kraft paper

(140gsm)

**Application temperature** +10 up to +40°C

**Temperature durability** -30 up to +80°C

**Durability** Up to 2 years

### **Standard Dimensions**

1370mm (wide) x 50m (long)

# **Safety Data Sheet**

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with teh regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After us, dispose of the waste product in accordance with local/national authorities.