



A EUROTECH GROUP BRAND

EVTEX

Item no. EV-ET365

Product Information

Introducing EVTEX, a versatile polyester-woven fabric designed for printing.

This 100% polyester fabric is compatible with eco-solvent, LATEX, and UV printing, featuring a removable and repositionable adhesive on the back for easy application.

It's ideal for indoor decoration, offering a block-out function to prevent color disturbance from the back side.

The semi-matte surface ensures high color density, and its PE coating on both sides keeps it safe from moisture-induced deformation.

With an acrylic-based adhesive, EVTEX provides permanent adhesion for long-lasting displays on various surfaces, including painted walls.

Shelf Life

1 year when stored in the original packaging between 10°C and 30°C at 65% relative humidity.

Recommendations for Laminating

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours before after printing.

Technical Data

Material	Semi-Matt Woven Polyester
Adhesive	Clear Acrylic-based
Thickness	305gsm
Application temperature	+10 up to +40°C
Temperature durability	-20 up to +70°C
Ink compatibility	Solvent, Eco, UV and Latex

Standard Dimensions

1370mm (wide) x 30m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.