

# EASY INSTALL SWIFT HIGH-TACK Item no. ET6-8000HT

## **Product Information**

The ST Easy Install Swift High Tack is a versatile 100-micron vinyl featuring an ultra-high-bond adhesive, making it ideal for low-energy surfaces such as PE-based trash bins. With its air egress design, this calendered vinyl ensures smooth and efficient installation. Available in gloss finish with a grey adhesive backing, it is also perfect for short-term indoor and outdoor uses, including signage, point-of-sale displays, and window graphics.

# **Shelf Life**

1 year when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

# **Recommendations for Laminating**

Please ensure the print is perfectly dry before laminating.

We suggest to let the material dry for at least 48 hours after printing.

## **Technical Data**

Carrier Monomeric white matt PVC

self-adhesive vinyl

Thickness 100  $\mu$  (+/- 5%)

Adhesive Grey removeable solvent-based

acrylic

Adhesion 14 N/cm

Liner Double-sided bubble-free PE

coated kraft paper (140 g/m<sup>2</sup>)

Application temperature +10 up to +40°C

Temperature durability -30 up to +80°C

Durability Up to 2 years

# **Standard Dimensions**

1370mm (wide) x 50m (long)

# **Safety Data Sheet**

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with teh regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After us, dispose of the waste product in accordance with local/national authorities.