



A EUROTECH GROUP BRAND

MAGSHEET

Item no. ET6-1106/7/8/9

Product Information

The Magsheet's extra-strong magnetic force ensures secure adhesion, making it ideal for outdoor signs and magnetic car door signs.

With a working temperature range of -20 to 60 degrees Celsius, it's built to withstand various weather conditions.

For vehicle applications, regular removal and cleaning are recommended to prevent dust buildup that could damage the magnetized surface.

Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

Technical Data

Face	Gloss PVC
Backing	Matt UV-coated magnet
Magnetisation	Isotropic
Surface Gauss	280 Gs (0.6mm) / 315 Gs (0.9mm)
Magnetic Pull	22g/cm ³ (0.6mm) / 39g/cm ³ (0.9mm)
Flexibility	No cracks when coiled around 1/2" radius
Hardness	Shore D 45

Standard Dimensions

0.6mm (thick) x 610mm (wide) x 15m (long)
0.6mm (thick) x 1000mm (wide) x 15m (long)
0.9mm (thick) x 610mm (wide) x 15m (long)
0.9mm (thick) x 1000mm (wide) x 15m (long)

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC). No. 1907/2006 and is available on request. This product is not hazardous with regards to transportation legislation. Neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with local/national authorities.

Eurotech Group
92-94 Radium Street
Welshpool 6106 WA

1800 30 61 61
info@eurotech.com.au
eurotech.com.au

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.